




I-CON wallbox is the JOINON solution for private and semi-public contexts, in compliance with the international standard IEC 61851-1 ed. 3. They are characterized by an elegant and compact design, for the special "one-hand recharge" functionality, and for the presence of the vandal-proof socket as an alternative to the connector with cable and holder integrated in the station, the IP55 degree combined with an IK10 certified resistance, intelligent load management, Backlight lighting, and various installation possibilities: wall, flush-mounting or floor.

INPUT			
Terminal blocks	3 x 10 mm ²	Socket/Connector Nr. (Type)	1 (Type 2 socket, with shutters)
Nominal akım	20 A	Charging activation	Free access
Total power	4.6 Kilowatt	Human Interface	RGB Led
		Connectivity	Hayır
OUTPUT		MECHANICAL FACTS	
Nominal voltaj	230 V	Mouting and installation	Wall mounting (floor mounting with support)
Current supplied (max)	20 A	Renk	Koyu gri
Maximum current	4.6 Kilowatt	Malzeme	Thermoplastic (Post-industrial origin)
Thermal-magnetic protection	Currently not present	External treatments	Hayır
Type of residual current protection	Currently not present	IP derecesi	IP55
Power meter	Currently not present	Direnç dayanıklı	IK10
DC Leakage check	Evet	Çalıştırma sıcaklığı	-25 +50 °C
(Auto)restart electrical protections	Currently not present	Customizations	Yes (front)

DIMENSIONAL



TECHNICAL SYMBOLOGY

IP

IP55

IK

IK10

STANDARDS/APPROVALS

